

# Rotaries for Custom Lock Assemblies



## Momentary

MFG. PART NUMBER	INNOVATION PART NUMBER	SWITCH CONFIGURATION												
CA4USE469	5930-7118	4PDT												
PINS 2 & 4 ARE COMMON PINS 6 & 8 ARE COMMON														
POSITION 1: 12:00		<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="4">12:00</td> <td>1 &amp; 2</td> <td>CLOSED</td> </tr> <tr> <td>3 &amp; 4</td> <td>OPEN</td> </tr> <tr> <td>5 &amp; 6</td> <td>CLOSED</td> </tr> <tr> <td>7 &amp; 8</td> <td>OPEN</td> </tr> </tbody> </table>	POSITION	PINS	STATE	12:00	1 & 2	CLOSED	3 & 4	OPEN	5 & 6	CLOSED	7 & 8	OPEN
POSITION	PINS	STATE												
12:00	1 & 2	CLOSED												
	3 & 4	OPEN												
	5 & 6	CLOSED												
	7 & 8	OPEN												
POSITION 2: 1:00 MOMENTARY		<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="4">1:00</td> <td>1 &amp; 2</td> <td>OPEN</td> </tr> <tr> <td>3 &amp; 4</td> <td>CLOSED</td> </tr> <tr> <td>5 &amp; 6</td> <td>OPEN</td> </tr> <tr> <td>7 &amp; 8</td> <td>CLOSED</td> </tr> </tbody> </table>	POSITION	PINS	STATE	1:00	1 & 2	OPEN	3 & 4	CLOSED	5 & 6	OPEN	7 & 8	CLOSED
POSITION	PINS	STATE												
1:00	1 & 2	OPEN												
	3 & 4	CLOSED												
	5 & 6	OPEN												
	7 & 8	CLOSED												

MFG. PART NUMBER	INNOVATION PART NUMBER	SWITCH CONFIGURATION												
CA4USM480	5933-7144	DPDT												
PINS 2 & 4 ARE COMMON PINS 6 & 8 ARE COMMON														
POSITION 1: 0°		<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="4">12:00</td> <td>1 &amp; 2</td> <td>CLOSED</td> </tr> <tr> <td>3 &amp; 4</td> <td>OPEN</td> </tr> <tr> <td>5 &amp; 6</td> <td>CLOSED</td> </tr> <tr> <td>7 &amp; 8</td> <td>OPEN</td> </tr> </tbody> </table>	POSITION	PINS	STATE	12:00	1 & 2	CLOSED	3 & 4	OPEN	5 & 6	CLOSED	7 & 8	OPEN
POSITION	PINS	STATE												
12:00	1 & 2	CLOSED												
	3 & 4	OPEN												
	5 & 6	CLOSED												
	7 & 8	OPEN												
POSITION 2: 45°		<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="4">1:30</td> <td>1 &amp; 2</td> <td>OPEN</td> </tr> <tr> <td>3 &amp; 4</td> <td>OPEN</td> </tr> <tr> <td>5 &amp; 6</td> <td>CLOSED</td> </tr> <tr> <td>7 &amp; 8</td> <td>CLOSED</td> </tr> </tbody> </table>	POSITION	PINS	STATE	1:30	1 & 2	OPEN	3 & 4	OPEN	5 & 6	CLOSED	7 & 8	CLOSED
POSITION	PINS	STATE												
1:30	1 & 2	OPEN												
	3 & 4	OPEN												
	5 & 6	CLOSED												
	7 & 8	CLOSED												

MFG. PART NUMBER	INNOVATION PART NUMBER	SWITCH CONFIGURATION												
CA4USM479	5933-1000	DPTT												
PINS 2 & 4 ARE COMMON PINS 6 & 8 ARE COMMON														
POSITION 1: 315°		<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="4">10:30</td> <td>1 &amp; 2</td> <td>OPEN</td> </tr> <tr> <td>3 &amp; 4</td> <td>OPEN</td> </tr> <tr> <td>5 &amp; 6</td> <td>OPEN</td> </tr> <tr> <td>7 &amp; 8</td> <td>CLOSED</td> </tr> </tbody> </table>	POSITION	PINS	STATE	10:30	1 & 2	OPEN	3 & 4	OPEN	5 & 6	OPEN	7 & 8	CLOSED
POSITION	PINS	STATE												
10:30	1 & 2	OPEN												
	3 & 4	OPEN												
	5 & 6	OPEN												
	7 & 8	CLOSED												
POSITION 2: 0°		<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="4">12:00</td> <td>1 &amp; 2</td> <td>OPEN</td> </tr> <tr> <td>3 &amp; 4</td> <td>CLOSED</td> </tr> <tr> <td>5 &amp; 6</td> <td>CLOSED</td> </tr> <tr> <td>7 &amp; 8</td> <td>OPEN</td> </tr> </tbody> </table>	POSITION	PINS	STATE	12:00	1 & 2	OPEN	3 & 4	CLOSED	5 & 6	CLOSED	7 & 8	OPEN
POSITION	PINS	STATE												
12:00	1 & 2	OPEN												
	3 & 4	CLOSED												
	5 & 6	CLOSED												
	7 & 8	OPEN												
POSITION 3: 45°		<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="4">1:30</td> <td>1 &amp; 2</td> <td>CLOSED</td> </tr> <tr> <td>3 &amp; 4</td> <td>OPEN</td> </tr> <tr> <td>5 &amp; 6</td> <td>CLOSED</td> </tr> <tr> <td>7 &amp; 8</td> <td>OPEN</td> </tr> </tbody> </table>	POSITION	PINS	STATE	1:30	1 & 2	CLOSED	3 & 4	OPEN	5 & 6	CLOSED	7 & 8	OPEN
POSITION	PINS	STATE												
1:30	1 & 2	CLOSED												
	3 & 4	OPEN												
	5 & 6	CLOSED												
	7 & 8	OPEN												

MFG. PART NUMBER	INNOVATION PART NUMBER	SWITCH CONFIGURATION												
CA4USE374	5930-7119	4PTT												
PINS 2 & 4 ARE COMMON PINS 6 & 8 ARE COMMON														
POSITION 1: 11:00 MOMENTARY		<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="4">11:00</td> <td>1 &amp; 2</td> <td>OPEN</td> </tr> <tr> <td>3 &amp; 4</td> <td>CLOSED</td> </tr> <tr> <td>5 &amp; 6</td> <td>OPEN</td> </tr> <tr> <td>7 &amp; 8</td> <td>CLOSED</td> </tr> </tbody> </table>	POSITION	PINS	STATE	11:00	1 & 2	OPEN	3 & 4	CLOSED	5 & 6	OPEN	7 & 8	CLOSED
POSITION	PINS	STATE												
11:00	1 & 2	OPEN												
	3 & 4	CLOSED												
	5 & 6	OPEN												
	7 & 8	CLOSED												
POSITION 2: 12:00		<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="4">12:00</td> <td>1 &amp; 2</td> <td>OPEN</td> </tr> <tr> <td>3 &amp; 4</td> <td>OPEN</td> </tr> <tr> <td>5 &amp; 6</td> <td>OPEN</td> </tr> <tr> <td>7 &amp; 8</td> <td>OPEN</td> </tr> </tbody> </table>	POSITION	PINS	STATE	12:00	1 & 2	OPEN	3 & 4	OPEN	5 & 6	OPEN	7 & 8	OPEN
POSITION	PINS	STATE												
12:00	1 & 2	OPEN												
	3 & 4	OPEN												
	5 & 6	OPEN												
	7 & 8	OPEN												
POSITION 3: 1:00 MOMENTARY		<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="4">1:00</td> <td>1 &amp; 2</td> <td>CLOSED</td> </tr> <tr> <td>3 &amp; 4</td> <td>OPEN</td> </tr> <tr> <td>5 &amp; 6</td> <td>CLOSED</td> </tr> <tr> <td>7 &amp; 8</td> <td>OPEN</td> </tr> </tbody> </table>	POSITION	PINS	STATE	1:00	1 & 2	CLOSED	3 & 4	OPEN	5 & 6	CLOSED	7 & 8	OPEN
POSITION	PINS	STATE												
1:00	1 & 2	CLOSED												
	3 & 4	OPEN												
	5 & 6	CLOSED												
	7 & 8	OPEN												

MFG. PART NUMBER	INNOVATION PART NUMBER	SWITCH CONFIGURATION																	
CA4USM159	5930-7219	3PTT																	
PINS 2 & 4 ARE COMMON PINS 6 & 8 ARE COMMON PINS 10 & 12 ARE COMMON																			
POSITION 1: 11:00 MOMENTARY		<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="8">11:00</td> <td>1 &amp; 2</td> <td>OPEN</td> </tr> <tr> <td>3 &amp; 4</td> <td>CLOSED</td> </tr> <tr> <td>5 &amp; 6</td> <td>OPEN</td> </tr> <tr> <td>7 &amp; 8</td> <td>CLOSED</td> </tr> <tr> <td>9 &amp; 10</td> <td>OPEN</td> </tr> <tr> <td>11 &amp; 12</td> <td>CLOSED</td> </tr> </tbody> </table>	POSITION	PINS	STATE	11:00	1 & 2	OPEN	3 & 4	CLOSED	5 & 6	OPEN	7 & 8	CLOSED	9 & 10	OPEN	11 & 12	CLOSED	
POSITION	PINS	STATE																	
11:00	1 & 2	OPEN																	
	3 & 4	CLOSED																	
	5 & 6	OPEN																	
	7 & 8	CLOSED																	
	9 & 10	OPEN																	
	11 & 12	CLOSED																	
	12:00 POSITION 2:		<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="8">12:00</td> <td>1 &amp; 2</td> <td>OPEN</td> </tr> <tr> <td>3 &amp; 4</td> <td>OPEN</td> </tr> <tr> <td>5 &amp; 6</td> <td>OPEN</td> </tr> <tr> <td>7 &amp; 8</td> <td>OPEN</td> </tr> <tr> <td>9 &amp; 10</td> <td>OPEN</td> </tr> <tr> <td>11 &amp; 12</td> <td>OPEN</td> </tr> </tbody> </table>	POSITION	PINS	STATE	12:00	1 & 2	OPEN	3 & 4	OPEN	5 & 6	OPEN	7 & 8	OPEN	9 & 10	OPEN	11 & 12	OPEN
	POSITION	PINS	STATE																
12:00	1 & 2	OPEN																	
	3 & 4	OPEN																	
	5 & 6	OPEN																	
	7 & 8	OPEN																	
	9 & 10	OPEN																	
	11 & 12	OPEN																	
	1:00 POSITION 3: MOMENTARY		<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="8">1:00</td> <td>1 &amp; 2</td> <td>CLOSED</td> </tr> <tr> <td>3 &amp; 4</td> <td>OPEN</td> </tr> <tr> <td>5 &amp; 6</td> <td>CLOSED</td> </tr> <tr> <td>7 &amp; 8</td> <td>OPEN</td> </tr> <tr> <td>9 &amp; 10</td> <td>CLOSED</td> </tr> <tr> <td>11 &amp; 12</td> <td>OPEN</td> </tr> </tbody> </table>	POSITION	PINS	STATE	1:00	1 & 2	CLOSED	3 & 4	OPEN	5 & 6	CLOSED	7 & 8	OPEN	9 & 10	CLOSED	11 & 12	OPEN
	POSITION	PINS	STATE																
1:00	1 & 2	CLOSED																	
	3 & 4	OPEN																	
	5 & 6	CLOSED																	
	7 & 8	OPEN																	
	9 & 10	CLOSED																	
	11 & 12	OPEN																	

MFG. PART NUMBER	INNOVATION PART NUMBER	SWITCH CONFIGURATION										
CA4USM478	5933-9125	TPTT										
PINS 2 & 4 ARE COMMON PINS 6 & 8 ARE COMMON												
POSITION 1: 315°		<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="3">10:30</td> <td>1 &amp; 2</td> <td>CLOSED</td> </tr> <tr> <td>5 &amp; 6</td> <td>OPEN</td> </tr> <tr> <td>7 &amp; 8</td> <td>OPEN</td> </tr> </tbody> </table>	POSITION	PINS	STATE	10:30	1 & 2	CLOSED	5 & 6	OPEN	7 & 8	OPEN
POSITION	PINS	STATE										
10:30	1 & 2	CLOSED										
	5 & 6	OPEN										
	7 & 8	OPEN										
POSITION 2: 0°		<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="3">12:00</td> <td>1 &amp; 2</td> <td>OPEN</td> </tr> <tr> <td>5 &amp; 6</td> <td>CLOSED</td> </tr> <tr> <td>7 &amp; 8</td> <td>OPEN</td> </tr> </tbody> </table>	POSITION	PINS	STATE	12:00	1 & 2	OPEN	5 & 6	CLOSED	7 & 8	OPEN
POSITION	PINS	STATE										
12:00	1 & 2	OPEN										
	5 & 6	CLOSED										
	7 & 8	OPEN										
POSITION 3: 45°		<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="3">1:30</td> <td>1 &amp; 2</td> <td>OPEN</td> </tr> <tr> <td>5 &amp; 6</td> <td>OPEN</td> </tr> <tr> <td>7 &amp; 8</td> <td>CLOSED</td> </tr> </tbody> </table>	POSITION	PINS	STATE	1:30	1 & 2	OPEN	5 & 6	OPEN	7 & 8	CLOSED
POSITION	PINS	STATE										
1:30	1 & 2	OPEN										
	5 & 6	OPEN										
	7 & 8	CLOSED										

MFG. PART NUMBER	INNOVATION PART NUMBER	SWITCH CONFIGURATION												
CA4USM895	593X-7319	DPTT												
PINS 2 & 4 ARE COMMON PINS 6 & 8 ARE COMMON														
POSITION 1: 11:00 MOMENTARY POSITION		<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="4">11:00</td> <td>1 &amp; 2</td> <td>OPEN</td> </tr> <tr> <td>3 &amp; 4</td> <td>CLOSED</td> </tr> <tr> <td>5 &amp; 6</td> <td>OPEN</td> </tr> <tr> <td>7 &amp; 8</td> <td>CLOSED</td> </tr> </tbody> </table>	POSITION	PINS	STATE	11:00	1 & 2	OPEN	3 & 4	CLOSED	5 & 6	OPEN	7 & 8	CLOSED
POSITION	PINS	STATE												
11:00	1 & 2	OPEN												
	3 & 4	CLOSED												
	5 & 6	OPEN												
	7 & 8	CLOSED												
POSITION 2: 12:00		<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="4">12:00</td> <td>1 &amp; 2</td> <td>CLOSED</td> </tr> <tr> <td>3 &amp; 4</td> <td>CLOSED</td> </tr> <tr> <td>5 &amp; 6</td> <td>OPEN</td> </tr> <tr> <td>7 &amp; 8</td> <td>OPEN</td> </tr> </tbody> </table>	POSITION	PINS	STATE	12:00	1 & 2	CLOSED	3 & 4	CLOSED	5 & 6	OPEN	7 & 8	OPEN
POSITION	PINS	STATE												
12:00	1 & 2	CLOSED												
	3 & 4	CLOSED												
	5 & 6	OPEN												
	7 & 8	OPEN												
POSITION 3: 1:00 MOMENTARY POSITION		<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="4">1:00</td> <td>1 &amp; 2</td> <td>CLOSED</td> </tr> <tr> <td>3 &amp; 4</td> <td>OPEN</td> </tr> <tr> <td>5 &amp; 6</td> <td>CLOSED</td> </tr> <tr> <td>7 &amp; 8</td> <td>OPEN</td> </tr> </tbody> </table>	POSITION	PINS	STATE	1:00	1 & 2	CLOSED	3 & 4	OPEN	5 & 6	CLOSED	7 & 8	OPEN
POSITION	PINS	STATE												
1:00	1 & 2	CLOSED												
	3 & 4	OPEN												
	5 & 6	CLOSED												
	7 & 8	OPEN												

# Rotaries for Custom Lock Assemblies



Maintained

MFG. PART NUMBER	2	INNOVATION PART NUMBER	SWITCH CONFIGURATION										
CA4USE598	1 2 3 90° THROW	5930-0017	DPTT										
POSITION 1: 9:00			<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="3">9:00</td> <td>1 &amp; 2</td> <td>CLOSED</td> </tr> <tr> <td>3 &amp; 4</td> <td>OPEN</td> </tr> <tr> <td>7 &amp; 8</td> <td>CLOSED</td> </tr> </tbody> </table>	POSITION	PINS	STATE	9:00	1 & 2	CLOSED	3 & 4	OPEN	7 & 8	CLOSED
POSITION	PINS	STATE											
9:00	1 & 2	CLOSED											
	3 & 4	OPEN											
	7 & 8	CLOSED											
POSITION 2: 12:00			<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="3">12:00</td> <td>1 &amp; 2</td> <td>CLOSED</td> </tr> <tr> <td>3 &amp; 4</td> <td>CLOSED</td> </tr> </tbody> </table>	POSITION	PINS	STATE	12:00	1 & 2	CLOSED	3 & 4	CLOSED		
POSITION	PINS	STATE											
12:00	1 & 2	CLOSED											
	3 & 4	CLOSED											
	POSITION 3: 3:00			<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="3">3:00</td> <td>1 &amp; 2</td> <td>OPEN</td> </tr> <tr> <td>3 &amp; 4</td> <td>OPEN</td> </tr> </tbody> </table>	POSITION	PINS	STATE	3:00	1 & 2	OPEN	3 & 4	OPEN	
POSITION	PINS	STATE											
3:00	1 & 2	OPEN											
	3 & 4	OPEN											

MFG. PART NUMBER	2	INNOVATION PART NUMBER	SWITCH CONFIGURATION												
CA4USE372	1 2 3 90° THROW	5930-1000	4PTT												
POSITION 1: 9:00			<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="4">9:00</td> <td>1 &amp; 2</td> <td>OPEN</td> </tr> <tr> <td>3 &amp; 4</td> <td>OPEN</td> </tr> <tr> <td>5 &amp; 6</td> <td>OPEN</td> </tr> <tr> <td>7 &amp; 8</td> <td>CLOSED</td> </tr> </tbody> </table>	POSITION	PINS	STATE	9:00	1 & 2	OPEN	3 & 4	OPEN	5 & 6	OPEN	7 & 8	CLOSED
POSITION	PINS	STATE													
9:00	1 & 2	OPEN													
	3 & 4	OPEN													
	5 & 6	OPEN													
	7 & 8	CLOSED													
POSITION 2: 12:00			<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="4">12:00</td> <td>1 &amp; 2</td> <td>OPEN</td> </tr> <tr> <td>3 &amp; 4</td> <td>CLOSED</td> </tr> <tr> <td>5 &amp; 6</td> <td>CLOSED</td> </tr> <tr> <td>7 &amp; 8</td> <td>OPEN</td> </tr> </tbody> </table>	POSITION	PINS	STATE	12:00	1 & 2	OPEN	3 & 4	CLOSED	5 & 6	CLOSED	7 & 8	OPEN
POSITION	PINS	STATE													
12:00	1 & 2	OPEN													
	3 & 4	CLOSED													
	5 & 6	CLOSED													
	7 & 8	OPEN													
POSITION 3: 3:00			<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="4">3:00</td> <td>1 &amp; 2</td> <td>CLOSED</td> </tr> <tr> <td>3 &amp; 4</td> <td>OPEN</td> </tr> <tr> <td>5 &amp; 6</td> <td>CLOSED</td> </tr> <tr> <td>7 &amp; 8</td> <td>OPEN</td> </tr> </tbody> </table>	POSITION	PINS	STATE	3:00	1 & 2	CLOSED	3 & 4	OPEN	5 & 6	CLOSED	7 & 8	OPEN
POSITION	PINS	STATE													
3:00	1 & 2	CLOSED													
	3 & 4	OPEN													
	5 & 6	CLOSED													
	7 & 8	OPEN													

MFG. PART NUMBER	2	INNOVATION PART NUMBER	SWITCH CONFIGURATION												
CA4USE572 REPLACES CA4USE306	1 2 3 90° THROW	5930-2124	4PTT												
POSITION 1: 9:00			<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="4">9:00</td> <td>1 &amp; 2</td> <td>OPEN</td> </tr> <tr> <td>3 &amp; 4</td> <td>CLOSED</td> </tr> <tr> <td>5 &amp; 6</td> <td>OPEN</td> </tr> <tr> <td>7 &amp; 8</td> <td>CLOSED</td> </tr> </tbody> </table>	POSITION	PINS	STATE	9:00	1 & 2	OPEN	3 & 4	CLOSED	5 & 6	OPEN	7 & 8	CLOSED
POSITION	PINS	STATE													
9:00	1 & 2	OPEN													
	3 & 4	CLOSED													
	5 & 6	OPEN													
	7 & 8	CLOSED													
POSITION 2: 12:00			<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="4">12:00</td> <td>1 &amp; 2</td> <td>OPEN</td> </tr> <tr> <td>3 &amp; 4</td> <td>CLOSED</td> </tr> <tr> <td>5 &amp; 6</td> <td>OPEN</td> </tr> <tr> <td>7 &amp; 8</td> <td>OPEN</td> </tr> </tbody> </table>	POSITION	PINS	STATE	12:00	1 & 2	OPEN	3 & 4	CLOSED	5 & 6	OPEN	7 & 8	OPEN
POSITION	PINS	STATE													
12:00	1 & 2	OPEN													
	3 & 4	CLOSED													
	5 & 6	OPEN													
	7 & 8	OPEN													
POSITION 3: 3:00			<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="4">3:00</td> <td>1 &amp; 2</td> <td>CLOSED</td> </tr> <tr> <td>3 &amp; 4</td> <td>OPEN</td> </tr> <tr> <td>5 &amp; 6</td> <td>CLOSED</td> </tr> <tr> <td>7 &amp; 8</td> <td>OPEN</td> </tr> </tbody> </table>	POSITION	PINS	STATE	3:00	1 & 2	CLOSED	3 & 4	OPEN	5 & 6	CLOSED	7 & 8	OPEN
POSITION	PINS	STATE													
3:00	1 & 2	CLOSED													
	3 & 4	OPEN													
	5 & 6	CLOSED													
	7 & 8	OPEN													

MFG. PART NUMBER	2	INNOVATION PART NUMBER	SWITCH CONFIGURATION												
CA4USE642 REPLACES CG4USE304	1 2 3 90° THROW	5930-5123	4PTT												
POSITION 1: 9:00			<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="4">9:00</td> <td>1 &amp; 2</td> <td>CLOSED</td> </tr> <tr> <td>3 &amp; 4</td> <td>CLOSED</td> </tr> <tr> <td>5 &amp; 6</td> <td>OPEN</td> </tr> <tr> <td>7 &amp; 8</td> <td>OPEN</td> </tr> </tbody> </table>	POSITION	PINS	STATE	9:00	1 & 2	CLOSED	3 & 4	CLOSED	5 & 6	OPEN	7 & 8	OPEN
POSITION	PINS	STATE													
9:00	1 & 2	CLOSED													
	3 & 4	CLOSED													
	5 & 6	OPEN													
	7 & 8	OPEN													
POSITION 2: 12:00			<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="4">12:00</td> <td>1 &amp; 2</td> <td>OPEN</td> </tr> <tr> <td>3 &amp; 4</td> <td>CLOSED</td> </tr> <tr> <td>5 &amp; 6</td> <td>CLOSED</td> </tr> <tr> <td>7 &amp; 8</td> <td>OPEN</td> </tr> </tbody> </table>	POSITION	PINS	STATE	12:00	1 & 2	OPEN	3 & 4	CLOSED	5 & 6	CLOSED	7 & 8	OPEN
POSITION	PINS	STATE													
12:00	1 & 2	OPEN													
	3 & 4	CLOSED													
	5 & 6	CLOSED													
	7 & 8	OPEN													
POSITION 3: 3:00			<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="4">3:00</td> <td>1 &amp; 2</td> <td>OPEN</td> </tr> <tr> <td>3 &amp; 4</td> <td>OPEN</td> </tr> <tr> <td>5 &amp; 6</td> <td>CLOSED</td> </tr> <tr> <td>7 &amp; 8</td> <td>CLOSED</td> </tr> </tbody> </table>	POSITION	PINS	STATE	3:00	1 & 2	OPEN	3 & 4	OPEN	5 & 6	CLOSED	7 & 8	CLOSED
POSITION	PINS	STATE													
3:00	1 & 2	OPEN													
	3 & 4	OPEN													
	5 & 6	CLOSED													
	7 & 8	CLOSED													

MFG. PART NUMBER	2	INNOVATION PART NUMBER	SWITCH CONFIGURATION												
CA4USE305	1 2 3 90° THROW	5930-5124	4PTT												
POSITION 1: 9:00			<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="4">9:00</td> <td>1 &amp; 2</td> <td>OPEN</td> </tr> <tr> <td>3 &amp; 4</td> <td>OPEN</td> </tr> <tr> <td>5 &amp; 6</td> <td>OPEN</td> </tr> <tr> <td>7 &amp; 8</td> <td>OPEN</td> </tr> </tbody> </table>	POSITION	PINS	STATE	9:00	1 & 2	OPEN	3 & 4	OPEN	5 & 6	OPEN	7 & 8	OPEN
POSITION	PINS	STATE													
9:00	1 & 2	OPEN													
	3 & 4	OPEN													
	5 & 6	OPEN													
	7 & 8	OPEN													
POSITION 2: 12:00			<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="4">12:00</td> <td>1 &amp; 2</td> <td>OPEN</td> </tr> <tr> <td>3 &amp; 4</td> <td>CLOSED</td> </tr> <tr> <td>5 &amp; 6</td> <td>CLOSED</td> </tr> <tr> <td>7 &amp; 8</td> <td>OPEN</td> </tr> </tbody> </table>	POSITION	PINS	STATE	12:00	1 & 2	OPEN	3 & 4	CLOSED	5 & 6	CLOSED	7 & 8	OPEN
POSITION	PINS	STATE													
12:00	1 & 2	OPEN													
	3 & 4	CLOSED													
	5 & 6	CLOSED													
	7 & 8	OPEN													
POSITION 3: 3:00			<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="4">3:00</td> <td>1 &amp; 2</td> <td>CLOSED</td> </tr> <tr> <td>3 &amp; 4</td> <td>OPEN</td> </tr> <tr> <td>5 &amp; 6</td> <td>OPEN</td> </tr> <tr> <td>7 &amp; 8</td> <td>CLOSED</td> </tr> </tbody> </table>	POSITION	PINS	STATE	3:00	1 & 2	CLOSED	3 & 4	OPEN	5 & 6	OPEN	7 & 8	CLOSED
POSITION	PINS	STATE													
3:00	1 & 2	CLOSED													
	3 & 4	OPEN													
	5 & 6	OPEN													
	7 & 8	CLOSED													

MFG. PART NUMBER	2	INNOVATION PART NUMBER	SWITCH CONFIGURATION										
CA4USE310	1 2 3 90° THROW	5930-9125	TPTT										
POSITION 1: 9:00			<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="3">9:00</td> <td>1 &amp; 2</td> <td>CLOSED</td> </tr> <tr> <td>5 &amp; 6</td> <td>OPEN</td> </tr> <tr> <td>7 &amp; 8</td> <td>OPEN</td> </tr> </tbody> </table>	POSITION	PINS	STATE	9:00	1 & 2	CLOSED	5 & 6	OPEN	7 & 8	OPEN
POSITION	PINS	STATE											
9:00	1 & 2	CLOSED											
	5 & 6	OPEN											
	7 & 8	OPEN											
POSITION 2: 12:00			<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="3">12:00</td> <td>1 &amp; 2</td> <td>OPEN</td> </tr> <tr> <td>5 &amp; 6</td> <td>CLOSED</td> </tr> <tr> <td>7 &amp; 8</td> <td>OPEN</td> </tr> </tbody> </table>	POSITION	PINS	STATE	12:00	1 & 2	OPEN	5 & 6	CLOSED	7 & 8	OPEN
POSITION	PINS	STATE											
12:00	1 & 2	OPEN											
	5 & 6	CLOSED											
	7 & 8	OPEN											
POSITION 3: 3:00			<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="3">3:00</td> <td>1 &amp; 2</td> <td>OPEN</td> </tr> <tr> <td>5 &amp; 6</td> <td>OPEN</td> </tr> <tr> <td>7 &amp; 8</td> <td>CLOSED</td> </tr> </tbody> </table>	POSITION	PINS	STATE	3:00	1 & 2	OPEN	5 & 6	OPEN	7 & 8	CLOSED
POSITION	PINS	STATE											
3:00	1 & 2	OPEN											
	5 & 6	OPEN											
	7 & 8	CLOSED											

MFG. PART NUMBER	2	INNOVATION PART NUMBER	SWITCH CONFIGURATION												
CA4USE C57660*E	1 2 180° THROW	5930-8144	4PDT												
POSITION 1: 9:00			<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="4">9:00</td> <td>1 &amp; 2</td> <td>CLOSED</td> </tr> <tr> <td>3 &amp; 4</td> <td>OPEN</td> </tr> <tr> <td>5 &amp; 6</td> <td>CLOSED</td> </tr> <tr> <td>7 &amp; 8</td> <td>OPEN</td> </tr> </tbody> </table>	POSITION	PINS	STATE	9:00	1 & 2	CLOSED	3 & 4	OPEN	5 & 6	CLOSED	7 & 8	OPEN
POSITION	PINS	STATE													
9:00	1 & 2	CLOSED													
	3 & 4	OPEN													
	5 & 6	CLOSED													
	7 & 8	OPEN													
POSITION 2: 3:00			<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="4">3:00</td> <td>1 &amp; 2</td> <td>OPEN</td> </tr> <tr> <td>3 &amp; 4</td> <td>CLOSED</td> </tr> <tr> <td>5 &amp; 6</td> <td>OPEN</td> </tr> <tr> <td>7 &amp; 8</td> <td>CLOSED</td> </tr> </tbody> </table>	POSITION	PINS	STATE	3:00	1 & 2	OPEN	3 & 4	CLOSED	5 & 6	OPEN	7 & 8	CLOSED
POSITION	PINS	STATE													
3:00	1 & 2	OPEN													
	3 & 4	CLOSED													
	5 & 6	OPEN													
	7 & 8	CLOSED													

MFG. PART NUMBER	2	INNOVATION PART NUMBER	SWITCH CONFIGURATION												
CA4USE195	1 2 90° THROW	5930-7144	4PDT												
POSITION 1: 12:00			<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="4">12:00</td> <td>1 &amp; 2</td> <td>CLOSED</td> </tr> <tr> <td>3 &amp; 4</td> <td>OPEN</td> </tr> <tr> <td>5 &amp; 6</td> <td>CLOSED</td> </tr> <tr> <td>7 &amp; 8</td> <td>OPEN</td> </tr> </tbody> </table>	POSITION	PINS	STATE	12:00	1 & 2	CLOSED	3 & 4	OPEN	5 & 6	CLOSED	7 & 8	OPEN
POSITION	PINS	STATE													
12:00	1 & 2	CLOSED													
	3 & 4	OPEN													
	5 & 6	CLOSED													
	7 & 8	OPEN													
POSITION 2: 3:00			<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="4">3:00</td> <td>1 &amp; 2</td> <td>OPEN</td> </tr> <tr> <td>3 &amp; 4</td> <td>CLOSED</td> </tr> <tr> <td>5 &amp; 6</td> <td>OPEN</td> </tr> <tr> <td>7 &amp; 8</td> <td>CLOSED</td> </tr> </tbody> </table>	POSITION	PINS	STATE	3:00	1 & 2	OPEN	3 & 4	CLOSED	5 & 6	OPEN	7 & 8	CLOSED
POSITION	PINS	STATE													
3:00	1 & 2	OPEN													
	3 & 4	CLOSED													
	5 & 6	OPEN													
	7 & 8	CLOSED													

MFG. PART NUMBER	2	INNOVATION PART NUMBER	SWITCH CONFIGURATION												
CA4USE533	1 2 180° THROW	5930-0014	4PDT												
POSITION 1: 9:00			<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="4">9:00</td> <td>1 &amp; 2</td> <td>CLOSED</td> </tr> <tr> <td>3 &amp; 4</td> <td>OPEN</td> </tr> <tr> <td>5 &amp; 6</td> <td>CLOSED</td> </tr> <tr> <td>7 &amp; 8</td> <td>OPEN</td> </tr> </tbody> </table>	POSITION	PINS	STATE	9:00	1 & 2	CLOSED	3 & 4	OPEN	5 & 6	CLOSED	7 & 8	OPEN
POSITION	PINS	STATE													
9:00	1 & 2	CLOSED													
	3 & 4	OPEN													
	5 & 6	CLOSED													
	7 & 8	OPEN													
POSITION 2: 3:00			<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="4">3:00</td> <td>1 &amp; 2</td> <td>OPEN</td> </tr> <tr> <td>3 &amp; 4</td> <td>CLOSED</td> </tr> <tr> <td>5 &amp; 6</td> <td>OPEN</td> </tr> <tr> <td>7 &amp; 8</td> <td>CLOSED</td> </tr> </tbody> </table>	POSITION	PINS	STATE	3:00	1 & 2	OPEN	3 & 4	CLOSED	5 & 6	OPEN	7 & 8	CLOSED
POSITION	PINS	STATE													
3:00	1 & 2	OPEN													
	3 & 4	CLOSED													
	5 & 6	OPEN													
	7 & 8	CLOSED													

MFG. PART NUMBER	2	INNOVATION PART NUMBER	SWITCH CONFIGURATION												
CA4USE307	1 2 3 90° THROW	5930-4124	4PDT												
POSITION 1: 9:00			<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="4">9:00</td> <td>1 &amp; 2</td> <td>CLOSED</td> </tr> <tr> <td>3 &amp; 4</td> <td>OPEN</td> </tr> <tr> <td>5 &amp; 6</td> <td>OPEN</td> </tr> <tr> <td>7 &amp; 8</td> <td>OPEN</td> </tr> </tbody> </table>	POSITION	PINS	STATE	9:00	1 & 2	CLOSED	3 & 4	OPEN	5 & 6	OPEN	7 & 8	OPEN
POSITION	PINS	STATE													
9:00	1 & 2	CLOSED													
	3 & 4	OPEN													
	5 & 6	OPEN													
	7 & 8	OPEN													
POSITION 2: 12:00			<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="4">12:00</td> <td>1 &amp; 2</td> <td>OPEN</td> </tr> <tr> <td>3 &amp; 4</td> <td>CLOSED</td> </tr> <tr> <td>5 &amp; 6</td> <td>OPEN</td> </tr> <tr> <td>7 &amp; 8</td> <td>OPEN</td> </tr> </tbody> </table>	POSITION	PINS	STATE	12:00	1 & 2	OPEN	3 & 4	CLOSED	5 & 6	OPEN	7 & 8	OPEN
POSITION	PINS	STATE													
12:00	1 & 2	OPEN													
	3 & 4	CLOSED													
	5 & 6	OPEN													
	7 & 8	OPEN													
POSITION 3: 3:00			<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="4">3:00</td> <td>1 &amp; 2</td> <td>OPEN</td> </tr> <tr> <td>3 &amp; 4</td> <td>OPEN</td> </tr> <tr> <td>5 &amp; 6</td> <td>OPEN</td> </tr> <tr> <td>7 &amp; 8</td> <td>CLOSED</td> </tr> </tbody> </table>	POSITION	PINS	STATE	3:00	1 & 2	OPEN	3 & 4	OPEN	5 & 6	OPEN	7 & 8	CLOSED
POSITION	PINS	STATE													
3:00	1 & 2	OPEN													
	3 & 4	OPEN													
	5 & 6	OPEN													
	7 & 8	CLOSED													
POSITION 4: 6:00			<table border="1"> <thead> <tr> <th>POSITION</th> <th>PINS</th> <th>STATE</th> </tr> </thead> <tbody> <tr> <td rowspan="4">6:00</td> <td>1 &amp; 2</td> <td>OPEN</td> </tr> <tr> <td>3 &amp; 4</td> <td>OPEN</td> </tr> <tr> <td>5 &amp; 6</td> <td>CLOSED</td> </tr> <tr> <td>7 &amp; 8</td> <td>OPEN</td> </tr> </tbody> </table>	POSITION	PINS	STATE	6:00	1 & 2	OPEN	3 & 4	OPEN	5 & 6	CLOSED	7 & 8	OPEN
POSITION	PINS	STATE													
6:00	1 & 2	OPEN													
	3 & 4	OPEN													
	5 & 6	CLOSED													
	7 & 8	OPEN													